



## SAFETY DATA SHEET EVO-STIK DECORATORS CAULK

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME EVO-STIK DECORATORS CAULK  
 PRODUCT NO. 635203, 635197  
 SUPPLIER BOSTIK LIMITED  
 COMMON ROAD  
 STAFFORD  
 STAFFORDSHIRE  
 ST16 3EH  
 +44 1785 255141  
 +44 1785 272650 (24 HOUR)  
 sds.uk@bostik.com

### 2 HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION R52/53.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
AMMONIA ...%	215-647-6	1336-21-6	< 1%	C;R34 N;R50
DIPROPYLENE GLYCOL DIBENZOATE		27138-31-4	< 1%	N;R51/53.
ETHANEDIOL	203-473-3	107-21-1	< 1%	Xn;R22
FORMALDEHYDE ...%	200-001-8	50-00-0	< 1%	Carc3;R40 T;R23/24/25 C;R34 R43
NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY; LOW BOILING	265-185-4	64742-82-1	1-5%	Xn;R65. N;R51/53. R10,R66.

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

#### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

#### SKIN CONTACT

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control.

## EVO-STIK DECORATORS CAULK

### SPECIFIC HAZARDS

Fire or high temperatures create: Toxic gases/vapours/fumes of Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Hydrocarbons.

### PROTECTIVE MEASURES IN FIRE

Wear self contained breathing apparatus

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Avoid skin and eye contact. Wear personal protective equipment.

### ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

### SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Runoff or release to sewer, waterway or ground is forbidden. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

### STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area. Do not store in direct sunlight.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
ETHANEDIOL	WEL		52 mg/m <sup>3</sup> (Sk)		104 mg/m <sup>3</sup> (Sk)
FORMALDEHYDE ...%	WEL	2 ppm	2.5 mg/m <sup>3</sup>	2 ppm	2.5 mg/m <sup>3</sup>

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

### HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Viton rubber (fluor rubber). Use thin cotton gloves inside the rubber gloves if allergy risk.

### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

### OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

### HYGIENE MEASURES

Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

## EVO-STIK DECORATORS CAULK

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste
RELATIVE DENSITY	1.47

### 10 STABILITY AND REACTIVITY

#### STABILITY

No particular stability concerns.

### 11 TOXICOLOGICAL INFORMATION

#### INHALATION

Vapour may irritate respiratory system or lungs.

#### SKIN CONTACT

Liquid may irritate skin.

#### EYE CONTACT

May cause eye irritation or physical damage

#### ROUTE OF ENTRY

Skin and/or eye contact.

### 12 ECOLOGICAL INFORMATION

#### ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment. Contamination of the terrestrial and aquatic environments should be avoided

### 13 DISPOSAL CONSIDERATIONS

#### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

### 14 TRANSPORT INFORMATION

#### GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

#### MARINE POLLUTANT

No.

### 15 REGULATORY INFORMATION

#### RISK PHRASES

R52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### SAFETY PHRASES

S36/37/39

Wear suitable protective clothing, gloves and eye/face protection.

S60

This material and its container must be disposed of as hazardous waste.

#### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

#### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### 16 OTHER INFORMATION

REVISION DATE: June 2007

SDS NO.: 13390

## EVO-STIK DECORATORS CAULK

### GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

### INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

### REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

### ISSUED BY

Approved EC

REVISION DATE June 2007

REV. NO./REPL. SDS GENERATED 3

DATE Sept 2006

### RISK PHRASES IN FULL

R10	Flammable.
R22	Harmful if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R37	Irritating to respiratory system.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R50	Very toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.