

Revision: 28 May 2014

SAFETY DATA SHEET

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: B2 Hand Foam/BuildBase B2 Hand Foam
- Product Part Number: 42755/42349

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Polyurethane foam
- Use advised against: No information available

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Fischer Fixing (UK) Ltd
- Address of Supplier: Hithercroft Road
Wallingford
Oxfordshire
OX10 9AT
- Telephone: 01491 827 920
- Fax: 01491 827 950
- Responsible Person: Mrs Mirka Valovicova MSc (Hons)
Technical Manager
- Email: Technical@fischer.co.uk

1.4 Emergency telephone number

- Emergency Telephone: 01491 827 920 (office hours only)

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

- Classification (REGULATION (EC) No 1272/2008) [CLP/GHS]: Flam. Aerosol 1, H222 - H229, Carc. 2, H351, Acute Tox. 4, H332, STOT RE 2, H373, Eye Irrit. 2, H319, STOT SE 3, H335, Skin Irrit. 2, H315, Resp Sens. 1, H334, Skin Sens. 1, H317
- Classification (67/548/EEC, 1999/45/EC) [CHIP]: F+; R12, Carc. Cat. 3; R40, Xn; R20, Xn; R48/20, Xi; R36/37/38, R42/43

2.2 Label elements



GHS02



GHS07



GHS08

- Contains polymethylene polyphenyl isocyanate
- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
- Signal Word: Danger
- Symbols: GHS02, GHS07, GHS08
- Hazard phrases
Extremely flammable aerosol.
Pressurised container: may burst if heated.
Suspected of causing cancer.
Harmful if inhaled.

Revision: 28 May 2014

SECTION 2 Hazards identification (....)

- May cause damage to organs through prolonged or repeated exposure by inhalation
- Causes serious eye irritation.
- May cause respiratory irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- Precautionary Phrases
 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 - Do not spray on an open flame or other ignition source.
 - Pressurized container: Do not pierce or burn, even after use.
 - Do not breathe dust/fume/gas/mist/vapours/spray.
 - Wear protective gloves/protective clothing/eye protection/face protection.
 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
 - Dispose of contents/container to an authorised waste collection point

2.3 Other hazards

- Contains isocyanates. May produce an allergic reaction.
- Store locked up/Keep out of reach of children.
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback

SECTION 3 Composition/information on ingredients**3.1 Substances****3.2 Mixtures**

- polymethylene polyphenol isocyanate
 - CAS Number: 9016-87-9
 - EC Number: N/A
 - Index No.: N/A
 - REACH Registration Number: N/A
 - Concentration: > 25%
 - Categories: Carc. 2, Acute Tox. 4, STOT RE 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Resp Sens. 1, Skin Sens. 1
 - R/H Phrases: H351, H332, H373, H319, H335, H315, H334, H317, R40, R20, R48/20, R36/37/38, R42/43
 - Symbols: GHS07, GHS08, Xn
- tris(2-chloro-1-methylethyl) phosphate
 - CAS Number: 13674-84-5
 - EC Number: 237-158-7
 - Index No.: N/A
 - REACH Registration Number: 01-2119447716-31-XXXX
 - Concentration: 1 - 25%
 - Categories: Acute Tox. 4
 - R/H Phrases: H302, R22
 - Symbols: GHS07, Xn
- propane
 - CAS Number: 74-98-6
 - EC Number: 200-827-9
 - Index No.: 601-003-00-5
 - REACH Registration Number: N/A
 - Concentration: 1 - 10%
 - Categories: Flam. Gas 1, Press. Gas
 - R/H Phrases: H220, H280, R12
 - Symbols: GHS02, GHS04, F+
- isobutane

Revision: 28 May 2014

SECTION 3 Composition/information on ingredients (....)

- CAS Number: 75-28-5
EC Number: 200-857-2
Index No.: 601-004-00-0
REACH Registration Number: N/A
Concentration: 1 - 10%
Categories: Flam. Gas 1, Press. Gas
R/H Phrases: H220, H280, R12
Symbols: GHS02, GHS04, F+
- dimethyl ether
CAS Number: 115-10-6
EC Number: 204-065-8
Index No.: 603-019-00-8
REACH Registration Number: 01-2119472128-37-XXX
Concentration: 1 - 10%
Categories: Flam. Gas 1, Press. Gas
R/H Phrases: H220, H280, R12
Symbols: GHS02, GHS04, F+
- 1,3-butadiene; buta-1,3-diene
CAS Number: 106-99-0
EC Number: 203-450-8
Index No.: 601-013-00-X
REACH Registration Number: N/A
Concentration: < 0.1%
Categories: Flam. Gas 1, Press. Gas, Carc. 1A, Muta. 1B
R/H Phrases: H220, H350, H340, R45, R46, R12
Symbols: GHS02, GHS04, GHS08, F+, T
-

SECTION 4 First aid measures

4.1 Description of first aid measures

- Contact with eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
- Contact with skin
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
- Ingestion
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
Give plenty of water to drink
Get medical advice/attention if you feel unwell.
- Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

- Causes allergic reaction in susceptible people
- Capable of causing respiratory sensitization
- Causes breathing difficulty
- Causes dry throat
- Severely irritating to eyes
- Lachrymatory

4.3 Indication of any immediate medical attention and special treatment needed

Revision: 28 May 2014

SECTION 4 First aid measures (....)

- Treat symptomatically
 - Wash affected area with plenty of polyethylene glycol
-

SECTION 5 Fire-fighting measures

5.1 Extinguishing media

- In case of fire: Use water spray, dry powder, sand or earth for extinction.
- In the event of an adjacent fire, cool containers with water spray

5.2 Special hazards arising from the substance or mixture

- Extremely Flammable
- Pressurized aerosol container
- In a fire or if heated, a pressure increase will occur and the container may burst
- Gives off irritating or toxic fumes (or gases) in a fire.
- May polymerise on exposure to heat
- Decomposition products may include phosphorous compounds and oxides of carbon
- Decomposition products may include hydrogen halides
- Decomposition products may include hydrogen cyanide

5.3 Advice for firefighters

- In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
 - Keep container(s) exposed to fire cool, by spraying with water
 - Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
 - Special protective equipment: Wear self-contained breathing apparatus (SCBA). Wear full protective clothing including chemical protection suit.
-

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Avoid breathing dust/fume/gas/mist/vapours/spray.
- May form explosive vapour/air mixtures
- Shut off all ignition sources
- Eyewash bottles should be available
- Wear protective clothing as per section 8

6.2 Environmental Precautions

- Do not allow to enter public sewers and watercourses
- Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

- Contain leaking liquid in earth or sand and remove to safe place when solid
- Remove by mechanical means
- Place in appropriate container
- Remove contaminated material to safe location for subsequent disposal
- Ventilate the area and wash spill site after material pick-up is complete
- Contaminated clothing should be laundered before reuse

6.4 Reference to other sections

- See Section 8 and 13
-

SECTION 7 Handling and storage

7.1 Precautions for safe handling

- Use only outdoors or in a well-ventilated area.
 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 -
-

Revision: 28 May 2014

SECTION 7 Handling and storage (....)

Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback

- Use non-sparking handtools
- Do not eat, drink or smoke when using this product.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2 Conditions for safe storage, including any incompatibilities

- Store at temperatures not exceeding 50°C/122°F. Keep cool.
- Protect from sunlight. Store in a well-ventilated place.
- Keep away from oxidisers, heat, flames or ignition sources
- Keep in highly flammable materials store
- Keep away from acids and alkalis
- Incompatible with amines

7.3 Specific end use(s)

- Polyurethane foam
-

SECTION 8 Exposure controls/personal protection**8.1 Control parameters**

- polymethylene polyphenol isocyanate
 - WEL (long term) 0.02 mg/m³ (UK EH40)
 - WEL (short term) 0.07 mg/m³ (UK EH40)
 - (Germany) MAK 0.05 mg/m³
- tris(2-chloro-1-methylethyl) phosphate
 - DNEL (dermal) 0.528 mg/kg (bw/day Acute systemic effects, Industry)
 - DNEL (inhalational) 0.93 mg/m³ (Acute systemic effects, Industry)
 - DNEL (dermal) 0.528 mg/kg (bw/day) Industry, Long Term, Systemic Effects
 - DNEL (inhalational) 0.93 mg/m³ Industry, Long Term, Systemic Effects
 - DNEL (dermal) 0.264 mg/kg (bw/day Acute systemic effects, Consumer)
 - DNEL (inhalational) 0.23 mg/m³ (Acute systemic effects, Consumer)
 - DNEL (Oral) 0.33 mg/kg (Acute systemic effects, Consumer)
 - DNEL (dermal) 0.264 mg/kg (bw/day) Consumer, Long Term, Systemic Effects
 - DNEL (inhalational) 0.23 mg/m³ Consumer, Long Term, Systemic Effects
 - DNEL (Oral) 0.33 mg/kg (bw/day) Consumer, Long Term, Systemic Effects
- propane
 - (Germany) MAK 1000 ml/m³ 1800 mg/m³
- isobutane
 - (Germany) MAK 1000 ml/m³ 2400 mg/m³
- dimethyl ether
 - WEL (long term) 400 ppm (UK EH40)
 - WEL (long term) 766 mg/m³ (UK EH40)
 - WEL (short term) 500 ppm (UK EH40)
 - WEL (short term) 958 mg/m³ (UK EH40)
 - (EC) OELV (long term TWA) 1000 ppm 1920 mg/m³
 - (Germany) MAK 1000 ml/m³ 1900 mg/m³

8.2 Exposure controls

- Engineering controls should be provided to prevent the need for ventilation
- Use explosion-proof ventilating and lighting equipment.
- Use good personal hygiene practices
- Do not eat, drink or smoke when using this product.

Revision: 28 May 2014

SECTION 8 Exposure controls/personal protection (....)


Respirator



Gloves



Goggles



Suit



No Smoking



No Flames

- In case of inadequate ventilation wear respiratory protection.
 - Where an air-purifying respirator is required, use EN 141, EN 405, EN 14387, Type A
 - Wear goggles giving complete eye protection
 - Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and standard EN 374.
 - Wear anti-static clothing and shoes
 - Eyewash bottles should be available
 - Keep working clothes separately and do not take them home
-

SECTION 9 Physical and chemical properties
9.1 Information on basic physical and chemical properties

- Appearance: Pressurized aerosol container
- Odour: No information available
- pH: No information available
- Melting point/Range: No information available
- Freezing point/Range: No information available
- Boiling Point/Range: No information available
- Flashpoint: No information available
- Evaporation Rate: No information available
- Flammability: Extremely flammable aerosol.
- Explosive Properties: No information available
- Vapour Pressure: No information available
- Vapour Density: Vapour density (air = 1) > 1
- Density: Density (water=1) 0.9
- Solubility in water: Insoluble in water
- Solubility in Fat: No information available
- Partition Coefficient (n-Octanol/Water): No information available
- Autoignition Temperature : No information available
- Viscosity: No information available
- Volatile Organic Compound Content 23%
- Oxidising Properties: No information available

9.2 Other information

- Bulk density 963 kg/m³
-

SECTION 10 Stability and reactivity
10.1 Reactivity

- Vapours may ignite
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
- Take precautionary measures against static discharge.

10.2 Chemical stability

- Considered stable under normal conditions

10.3 Possibility of hazardous reactions

- In use, may form flammable/explosive vapour-air mixture
 - May polymerise on exposure to heat
 - Reacts violently with acids and alkalis
-

Revision: 28 May 2014

SECTION 10 Stability and reactivity (....)

Reacts with amines

10.4 Conditions to avoid

- Do not store above 50 °C
- Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- Use non-sparking handtools

10.5 Incompatible materials

- Incompatible with acid
- Incompatible with alkalis (strong bases)
- Incompatible with amines
- Incompatible with oxidizing substances

10.6 Hazardous Decomposition Products

- Decomposition products may include carbon oxides
 - Decomposition products may include hydrogen halides
 - Decomposition products may include hydrogen cyanide
 - Decomposition products may include phosphorous oxides
 - Decomposition products may include nitrogen oxides
-

SECTION 11 Toxicological information

11.1 Information on toxicological effects

Acute Toxicity

- No experimental test data available for the mixture
- LD50 (oral,rat) (polymethylene polyphenol isocyanate) > 10000 mg/kg
- LD50 (dermal) : (rabbit) (polymethylene polyphenol isocyanate) > 5000 mg/kg
- LC50 (inhalation,rat) (polymethylene polyphenol isocyanate) 10 - 20 mg/l/4h
- LD50 (oral,rat) (tris(2-chloro-1-methylethyl) phosphate) 1011 - 1824 mg/kg
- LD50 (dermal,rabbit) (tris(2-chloro-1-methylethyl) phosphate) > 2000 mg/kg
- LC50 (inhalation,rat) (tris(2-chloro-1-methylethyl) phosphate) > 5 mg/l/4h
- LC50 (inhalational, rat) : (propane) > 800000 ppm/15 minutes
- LC50 (inhalation,rat) (isobutane) > 50 mg/l/4h
- LC50 (inhalation,rat) (dimethyl ether) 309 mg/l/4h
- LC50 (inhalation, rat) (dimethyl ether) 163991 ppm/4h

Skin corrosion/irritation

- No experimental test data available for the mixture
- Irritation (dermal, rabbit) 0.5ml/4h test score (tris(2-chloro-1-methylethyl) phosphate) - non irritant
- Irritation (dermal, rabbit) 0.5ml/4h test score (polymethylene polyphenyl isocyanate) - irritant

Serious eye damage/irritation

- No experimental test data available for the mixture
- Irritation (eye, rabbit) (tris(2-chloro-1-methylethyl) phosphate) - non irritant
- Irritation (eye, rabbit) (polymethylene polyphenyl isocyanate) - irritant

Respiratory or skin sensitisation

- No experimental test data available for the mixture
- Sensitization (guinea pig) : (polymethylene polyphenyl isocyanate) (skin) Positive
- Sensitization (guinea pig) : (polymethylene polyphenyl isocyanate) (inhalation) Positive

Germ cell mutagenicity

- No evidence of mutagenic effects

Carcinogenicity

- Category 2 Carcinogen

Revision: 28 May 2014

SECTION 11 Toxicological information (....)

Reproductive toxicity

- No evidence of reproductive effects

Specific target organ toxicity (STOT) - single exposure

- STOT SE 3
- May cause respiratory irritation

Specific target organ toxicity (STOT) - repeated exposure

- STOT RE 2
- May cause damage to organs through prolonged or repeated exposure by inhalation

Aspiration hazard

- No information available

Contact with eyes

- Causes severe irritation
- Causes redness
- Lachrymatory

Contact with skin

- May cause allergic reaction in susceptible people
- May cause irritation
- In cases of severe exposure, dermatitis may develop

Ingestion

- The ingestion of significant quantities may cause nausea/vomiting

Inhalation

- May cause asthma
 - May cause breathing difficulty
 - In cases of severe exposure, delayed pulmonary oedema may develop
 - Prolonged exposure may cause abrasive irritation of the mucous membranes
-

SECTION 12 Ecological information

12.1 Toxicity

- No experimental test data available for the mixture
- LC50 (fish) (polymethylene polyphenyl isocyanate) > 1000 mg/l (96 hr)
- EC50 (activated sludge) (polymethylene polyphenol isocyanate) > 100 mg/l
- LC50 (fish)(brachydanio rerio) (tris(2-chloro-1-methylethyl) phosphate) 56.2 mg/l (96 hr)
- EC50 (Daphnia magna) (tris(2-chloro-1-methylethyl) phosphate) 65 - 335 mg/l (48 hr)
- EC50 (Pseudokirchneriella subcapitata) (tris(2-chloro-1-methylethyl) phosphate) 73 mg/l (96 hr)
- LC50 (fish) (propane) 24 mg/l (96 hr)
- EC50 (Daphnia magna) (propane) 7 mg/l (48 hr)
- IC50 (algae) (propane) 8 mg/l (72 hr)
- EC50 (activated sludge) (propane) 10 - 100 mg/l
- EC0 (Fathead minnow) (propane) 2.4 - 3.7 mg/l (768 hr)
- EC0 (Daphnia magna) (propane) 1.1 - 2.0 mg/l (504 hr)
- LC50 (fish) (dimethyl ether) > 1000 mg/l (96 hr)
- LC50 (Daphnia magna) (dimethyl ether) > 4400 mg/l (48 hr)

12.2 Persistence and degradability

- Not readily biodegradable
 - OECD 301A: DOC Die-Away 5 % 28 day(s) (dimethyl ether)
 - OECD 301C: MITI (I) 0 % 28 day(s) (tris(2-chloro-1-methylethyl) phosphate)
 - OECD 302C: Inherent Biodegradability: Modified MITI Test (II) < 60% (polymethylene polyphenyl isocyanate)
 -
-

Revision: 28 May 2014

SECTION 12 Ecological information (....)

OECD 301E: Modified OECD Screening 14 % 28 day(s) (tris(2-chloro-1-methylethyl) phosphate)

- OECD 301E: Modified OECD Screening 70 % - day(s) (propane)
- Biodegradation test, water, other 70% < 10 day(s) (propane)
- Biodegradation test, water, other 72.6% 35 day(s) (isobutane)
- Biodegradation test, water, other 50% 16 - 26 day(s) (isobutane)
- Soil half-life (T1/2) 2/15 (QSAR) days (dimethyl ether)

12.3 Bioaccumulation Potential

- Not available
- Log Kow - No data available for the mixture
- Log Kow - 2.59 (tris(2-chloro-1-methylethyl) phosphate)
- Log Kow - 2.76 - 2.88 (isobutane)
- Log Kow - 0.10 (dimethyl ether)
- BCF (cyprinus carpio) 0.8 - 4.6 (tris(2-chloro-1-methylethyl) phosphate)
- BCF (fish) 1 (polymethylene polyphenyl isocyanate)
- BCF (fish) 9 - 25 (propane, QSAR)
- BCF (fish) 20 - 52 (isobutane)
- BCF (daphnia magna) 20 - 52 (isobutane)

12.4 Mobility in soil

- No information available

12.5 Results of PBT and vPvB assessment

- No information available

12.6 Other Adverse Effects

- Water Hazard Class WGK 1 - low hazard to waters (Germany)
-

SECTION 13 Disposal considerations**13.1 Waste treatment methods**

- Avoid release to the environment.
- Dispose of contents/container to an authorised waste collection point
- Disposal should be in accordance with local, state or national legislation

13.2 Classification

- Waste Codes in accordance with the European Waste catalogue (EWC) are origin-defined. Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
-

SECTION 14 Transport information

Flammable gas.

14.1 UN Number

- UN No.: 1950

14.2 Proper Shipping Name

- Proper Shipping Name: AEROSOLS

14.3 Transport hazard class(es)

- Hazard Class: 2

14.4 Packing group

Revision: 28 May 2014

SECTION 14 Transport information (....)

- Packing Group: N/A
- 14.5 Environmental hazards
 - No information available
- 14.6 Special precautions for user
 - See Section 7
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code
 - Not applicable
- 14.8 Road/Rail (ADR/RID)
 - ADR UN No.: 1950
 - Proper Shipping Name: AEROSOLS
 - ADR Hazard Class: 2
 - ADR Packing Group: N/A
 - Tunnel Code: D
- 14.9 Sea (IMDG)
 - IMDG UN No.: 1950
 - Proper Shipping Name: AEROSOLS
 - IMDG Hazard Class: 2
 - IMDG Pack Group.: N/A
- 14.10 Air (ICAO/IATA)
 - ICAO UN No.: 1950
 - Proper Shipping Name: AEROSOLS, FLAMMABLE
 - ICAO Hazard Class: 2.1
 - ICAO Packing Group: N/A

SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- This Safety Data Sheet is provided in compliance with the EC Directive 1907/2006-453/2010
 - Restrictions on use according to Annex XVII to REACH Regulation: Entry 3 - Liquid dangerous substances which are regarded as dangerous., Shall not be used in ornamental articles intended to produce light or colour effects by means of different phases; tricks and jokes; games for one or more participants, or any such article intended to be used as such, even with ornamental aspects., Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they can be used as fuel in decorative oil lamps for supply to the general public; and, present an aspiration hazard and are labelled with R65 or H304., Entry 40 - Flammable substances in aerosol generators for entertainment and decorative purposes., Shall not be used, as substances or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes., Entry 56 - Methylendiphenyl diisocyanate (MDI), Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0.1% by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging:
 - (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC (*****); (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures:
 - '— Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
 - Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

Revision: 28 May 2014

SECTION 15 Regulatory information (....)

— This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.'

- Volatile Organic Compound Content 23%
- Water Hazard Class WGK 1 - low hazard to waters (Germany)

15.2 Chemical Safety Assessment

- A REACH chemical safety assessment has not been carried out
-

SECTION 16 Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated. H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled. H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335: May cause respiratory irritation. H340: May cause genetic defects. H350: May cause cancer. H351: Suspected of causing cancer. H373: May cause damage to organs through prolonged or repeated exposure. R12: Extremely Flammable. R20: Harmful by inhalation. R22: Harmful if swallowed. R36/37/38: Irritating to eyes, respiratory system and skin. R40: Limited evidence of carcinogenic effect. R42/43: May cause sensitisation by inhalation and skin contact. R45: May cause cancer. R46: May cause heritable genetic damage. R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.