



## Product information

<b><u>Application</u></b>	Elevator travelling cable for indoor and panoramic elevators. Supports all Cat.6/Class E applications (e.g. 10 Base-T, 100 Base-T, 1000 Base-T, ISDN). Max. channel length 65 m (transceiver to receiver).	
<b><u>Installation</u></b>	Follow instructions in Dynofil manual for proper handling and installation Suspension device: LZ 1006 Loop diameter: natural loop	
<b><u>Construction</u></b>	Pairs AWG 26: Support members: Outer sheath:	PE, Al/PETP foil, overall tinned Cu braid shield (S/FTP) none PVC
<b><u>Mechanical properties</u></b>	Free suspension length: Travel speed: Operating temperature: Overall dimension (approx.): Total weight (approx.): Copper content:	max. 45 m max. 4 m/s -15 to +70 °C 29.6 x 8.4 mm 332 kg/km 70 kg/km
<b><u>Electrical properties</u></b>	Rated voltage $U_0/U$ : Pairs AWG 26:	100/100 V
<b><u>Properties of data elements</u></b>	Pairs AWG 26:	see type HF-4367-F
<b><u>Fire performance</u></b>	Flame propagation:	IEC/EN 60332-1-2
<b><u>Colour code</u></b>	Pairs AWG 26: Outer sheath:	white/blue, red/orange, black/green, yellow/brown (4x) grey
<b><u>Standard</u></b>	With reference to EN 50214	

Part no.	Type	No./size of conductors
191 032	8867-F	4 x 4 x 2 x AWG 26 (S/FTP)