

EN 81-70

TENTED

LCD Display







ICARO

Landing LCD position indicator

MAIN FEATURES

- LCD Model: indicator available in blue or black background.
- Fast Fixing: frontal mounting with frame or flush mounting on 1.2 and 2mm faceplates through soldered studs
- Screen: polycarbonate lens (shock-proof)
- Colours: white LED on blue background or 5 different colours (navy blue, white, yellow, green and red) on black background.
- Wiring: screws or pre-wired connectors (AMP or JST)
- Common: positive or negative
- Power supply: 12/24Vdc +/- 10%
- Signals: floors, arrows, out of service
- Optional signals: sent alarm and overload signal
- Integrated and programmable three-tone chime
- Easy programming by a dedicated integrated keyboard
- 32 stops in binary code, 11 stops 1 wire for floor
- 64 stops in independent mode (magnetic sensors)
- Up and down arrow (40,5mm)
- Available in CAN and RS485 serial version
- Possibility to implement binary, inverted binary, BCD, Gray and 7 segments codes

COLOURS


LEGEND/ARROW: White, yellow, aquamarine, red and green



FRAME - Chrome / Gold / Anthracite



OPTIONS - Vandal proof glass for the flush mounting version





PEW Electrical Distributors Ltd Unit 1 The iO Centre 59-71 River Road Barking, Essex IG11 ODR

0208 507 1001 sales@pewelectrical.com www.pewelectrical.com

