



PEW Electrical
Distributors

Slim LED Batten

mains only and emergency lighting

An elegant low-profile LED batten range with superior light output and energy saving performance over traditional fluorescent solutions.

Featuring Epistar high power LEDs with 4000K natural white illumination for excellent colour rendition.



All battens are easy to affix using external stainless steel clamps and also come pre-wired for easy termination into a switch/joint box.

Slim profile at only 24mm deep in an aluminium housing.



Technical Batten

Supply Voltage : 200-240 v AC 50/60 HZ
Total Power : 18W \pm 5% // 27W \pm 5% // 36W \pm 5%
Total Lumens : 18W = 1600 LM \pm 5%
27W = 2200 LM \pm 5% // 36W = 3200 LM \pm 5%
CRI : > 80 Ra
CCT (output Colour temperature) : 4000k-NW
Power factor : > 0.95
Beam Angle : 110°

Technical Emergency Pack

Supply Voltage : 200-240 v AC 50/60 HZ
Constant Emergency Power : 5W
Battery : NI-Mh 9.6V 2200mAh Built in Battery
Recharge time : <12Hr Minimum
Duration : >180Min
Charge Current : 200mA +/-10%
Charge Power : 4 watt

Easy-to-order PEW codes

SLB1806 - 2ft 18W Dimensions: 600 x 75 x 24mm

SLB2709 - 3ft 27W Dimensions: 900 x 75 x 24mm

SLB3612 - 4ft 36W Dimensions: 1200 x 75 x 24mm

EL05UPK - 5W LED Emergency Pack (1 per Batten)

A compact 5W Emergency Back-Up Power Unit providing 3 Hours Maintained operation fully compliant to BS 5266-1:2011.



Emergency Pack **EL05UPK**

PEW Electrical Distributors Ltd

Unit 1 The iO Centre
59-71 River Road
Barking, Essex IG11 0DR

0208 507 1001

sales@pewelectrical.com
www.pewelectrical.com

