



B-LIFT 400 EVO

EN 81-20 EN 81-50

Lift light curtains compliant to EN81-20/50 standard, with self-test function and with the opportunity to exchange the position of transmitter with that of receiver.

MAIN FEATURES

- Size (WxDxH): 10x23.5x2000mm.
- Detecting Height: 20mm to 1872mm.
- Number of IR diodes: 40.
- Scan beams (distance > 400mm): 194 beams.
- Scan beams (distance < 400mm): 118 beams.
- Opening: 0mm - 4000mm.
- Ideal for both static and dynamic mounting.
- Light Immunity: 100,000 LUX.
- Operating Temperature: -20°C ~ +65°C.
- Buzzer: after continuous detection for 15s buzzer on (when BUZZER SWITCH=ON).
- Cable length: 4 mtr.
- Automasking function: 1635-1800mm (optional).
- Standard output: relay.
- Test output: relay.
- IP: 54.



FOCUS



UP TO 194 BEAMS



SELF TEST FUNCTION



IDEAL FOR SUNNY ENVIORNMENTS



AUTOMASKING FUNCTION / OPTIONAL

MODEL	POWER SUPPLY	AUTOMASKING FUNCTION
B-LIFT 402-E	220 VAC	
B-LIFT 418-E	12/24 VDC	
B-LIFT 402-EA	220 VAC	√
B-LIFT 418-EA	12/24 VDC	√

